

Most Android phones have the same menu, so you have to find these basics steps in the <settings menu>

- <settings>
- <wireless & networks>
- <mobile networks>
- <access point names>
- <new APN>
- <name>
 - click on <name> and enter your carriers name
 - tmobile, simple mobile, h2o, at&t
- <APN>
 - click on <APN> and enter your carrier's APN name
 - tmobile = epc.tmobile.com
 - simple = simple
 - h2o = att.mvno
 - at&t = wap.cingular
- <proxy>
 - click on <proxy> and enter your carrier's proxy numbers
 - tmobile = 216.155.165.050
 - simple = 216.155.165.050
 - h2o = 066.209.011.033
 - at&t = 066.209.011.061
- <port>
 - click on <port> and enter your carrier's port number
 - tmobile = 80
 - simple = 8080
 - h2o = 80
 - at&t = 80
- <username>
 - Leave the user name on empty
- <password>
 - leave the password on empty
- <server>
 - leave the server on empty
- <mmsc>
 - tmobile = <http://mms.msg.eng.t-mobile.com/mms/wapenc>
 - simple = <http://mms.msg.eng.t-mobile.com/mms/wapenc>
 - h2o = <http://mmsc.cingular.com>
 - at&t = <http://mmsc.cingular.com>
- <mms proxy>
 - click on <mms proxy> and enter your carrier's proxy numbers
 - tmobile = 216.155.165.050
 - simple = 216.155.165.050
 - h2o = 066.209.011.033
 - at&t = 066.209.011.061
- <mms port>
 - click on <mms port> and enter your carrier's port number
 - tmobile = 80
 - simple = 8080
 - h2o = 80
 - at&t = 80
- <mcc>
 - tmobile = 310
 - simple = 310
 - h2o = 310
 - at&t = 310
- <mnc>
 - tmobile = 260
 - simple = 260
 - h2o = 410
 - at&t = 410

